

# Model **B23**



## B23 Model Overview

Perfect for users looking for carbureted, commercial mowing power. The B23 features a new chassis and body design reducing weight and accentuating hillside stability and the Walker beautiful cut.

<b>Ideal Application:</b> .....	Commercial and Rural Properties
<b>Type</b> .....	Non-Collection
<b>Power</b> .....	22.5 HP
<b>Engine</b> .....	Rehiko Command Pro® CH680
<b>Engine Displacement</b> .....	674 cc (41.1 cu. in.)
<b>Max Power</b> .....	22.5 HP @ 3600 RPM
<b>Max Torque</b> .....	36.8 ft-lbs
<b>Fuel</b> .....	Gasoline (unleaded - min. 87 octane)
<b>Fuel Capacity</b> .....	4.7 U.S. gal (17.8 liter)
<b>Cooling System</b> .....	Air
<b>Length, Tractor Only</b> .....	63 in (160 cm)
<b>Length, Tractor with M48 Deck</b> .....	90.75 in (230 cm)
<b>Width, Tractor Only (Outside Tire)</b> .....	38.5 in (98 cm)
<b>Width, Tractor with M48 Deck</b> .....	49 in (125 cm)
<b>Height, Tractor</b> .....	39.5 in (100 cm)
<b>Weight, Tractor Only</b> .....	600 lbs (272 kg)
<b>Weight, Tractor with M48 Deck</b> .....	806 lbs (366 kg)

Model may be shown with optional add-ons.

## Decks

Discharge: S36, S42, S48, S52, S56, S60, S74

Mulching: M36, M42, M42B, M48, M52, M52K, M60K

## Attachments

Dozer Blade, Single-Stage Snowblower, Boom Sprayer, Spkyer Spreader, Dethatcher, Soft Cab

## Implements

Implement Hitch, Dozer Blade, Two-Stage Snowblower, Debris Blower, Rotary Broom

## Options

18 x 7.00-8 Turf Tire, 18 x 7.00-8 Directional AT Tire, 18 x 8.5-10 Turf Tire\*, 18 x 8.5-10 AT Tire, 18 x 9.5-8 Turf Tire, 18 x 10.5-10 Turf Tire, 18 x 11.00-10 AT Tire, Tire Chains, Pneumatic Deck Tire, Big Tire Kit, Comfort Seat\*, Suspension Seat, Steering Lever Extensions, Armrests, Cup Holder, Headlights, Adjustable Footrests, Deck Height Washers, Deck Height Adjuster, Curb Jumper, Break Away Blades, Tow Hitch, Accelerator® Grass Catcher, Utility Bed, Tail Weights, Manual Deck Lift  
*\*Standard on this model.*



See more information at [walker.com](http://walker.com)

Price with options and add-ons as displayed.